

Prism Upholstery 34143



1554 LINEN




3225 CHERRY



0955 NUGGET




3535 BRANDY



1744 CARIBBEAN



3515 GRANITE



0614 SLATE

Moguls Upholstery 2386



2057 GREEN APPLE



2197 GRAPHITE



2188 FLARE



2196 COFFEE BEAN



2190 HONEY COMB



2193 BLUE STAR



2198 ONYX



2194 THISTLE

Open House

Upholstery 2334



2048 GREEN OLIVE




2087 GREEN APPLE



2035 ANCORÀ



2036 STRAW



2014 RED DELICIOUS



2049 GOOSE



2020 AMBER



2065 THISTLE



2083 COFFEE BEAN



2053 ASTEROID



2044 MULBERRY



2025 MIDNIGHT



2016 ONYX

Upholstery Specifications

Style	OPEN HOUSE 2334 GRADE 1	PRISM 34143 GRADE 1	MAGUS 2386 GRADE 1
Contents	100% recycled polyester	100% recycled polyester	100% recycled polyester
Weight	12.4 ± 1.6 oz./lin. yd.	10.5 ± 0.5 oz./lin. yd.	13.4 ± 1.0 oz./lin. yd.
Width	54" min. usable	54" min. usable	54" min. usable
Revert	none	none	5.2" vertical, 26.7" horizontal
Backing	none	none	none
Treatment	none	BLOCK , ¹ dur-1	none
Cleaning Code	W5	W5	W5
	Clean with water-based cleaning agents, foam or pump, water-free solvents. Vacuuming or light brushing is recommended to prevent dust and soil buildup.	Clean with water-based cleaning agents, foam or pump, water-free solvents. Vacuuming or light brushing is recommended to prevent dust and soil buildup.	Clean with water-based cleaning agents, foam or pump, water-free solvents. Vacuuming or light brushing is recommended to prevent dust and soil buildup.
Performance			
Breaking strength (ASTM D5634)	275 lbs. min. warp and fill	200 lbs. min. warp, 175 lbs. min. fill	250 lbs. min. warp, 140 lbs. min. fill
Tear (ASTM D2265)	25 lbs. min. warp and fill	25 lbs. min. warp and fill	20 lbs. min. warp and fill
Seam Slippage (ASTM D4034)	50 lbs. min. warp and fill	40 lbs. min. warp, 50 lbs. min. fill	60 lbs. min. warp and fill
Filling resistance (ASTM D3511)	class 4 min.	class 4 min.	class 4 min.
Colorfastness to light (AATCC 16 Option 3)	40 hrs. min.	40 hrs. min.	40 hrs. min.
Colorfastness to crocking (AATCC 8)	class 4 min. dry, class 3 min. wet	class 4 min. dry, class 3 min. wet	class 4 min. dry, class 3 min. wet
Colorfastness to water (AATCC 167)	class 3 min. for staining, class 4 min. for color change	class 3 min. for staining, class 4 min. for color change	class 3 min. for staining, class 4 min. for color change
Abrasion resistance (ASTM D4587)	200,000 double rubs - cotton duck	100,000 double rubs - 90/10 duck	100,000 double rubs - cotton duck
Flammability			
State of CA, Tech. Bulletin, 117 666.6	passes	passes	passes
UFAC	class 1	class 1	class 1
NFPA 283	class 1	class 1	class 1

Colors may vary slightly between dye lots. Magus and Prism are decorative fabrics. Application testing of these products is recommended.



Tennex® is a registered trademark of InterfaceFABRIC™, Inc. 2007 and designates fabric that are made from 100% recycled or compostable material using increasingly sustainable manufacturing practices to produce a high quality product that is recyclable at the end of its useful life. www.tennex.com



100% of the electricity used to make the Open House and Magus is matched by GREENE certified Renewable Energy Certificates www.green-e.org.

BLOCK,¹dur-1

Formulated by InterfaceFABRIC, BLOCKade is a durable water and oil resistant treatment formulated for commercial upholstery fabrics. Liquid spills will bead up on the surface of the fabric so that they can be removed before they stain the fibers.